


Double Row Cylindrical Roller Bearing

VISTA®
Bearing



NN
圆柱孔

Cuscinetto NO.	Vecchio n.	Dimensioni perimetrali [mm]					Coefficienti di carico di base (kN)		Velocità limite (rpm)		Peso (kg)
		d	D	B/C	rs min	r2smin	Cr	Cor	Grasso	Olio	
NN4830	-	150	190	40	1.1	1.1	190	450	2400	3000	2.8
NN4830K	-	150	190	40	1.1	1.1	190	450	2400	3000	2.75
NNU4930	4482930	150	210	60	2	2	300	590	2000	2600	6.3
NNU4930K	4382930	150	210	60	2	2	300	590	2000	2600	6.2
NN3030	3282130	150	225	56	2.1	2.1	330	570	2000	2600	7.8
NN3030K	3182130	150	225	56	2.1	2.1	330	570	2000	2600	7.7
NNU4130	-	150	250	100	2.1	2.1	680	1170	1900	2400	18
NNU4130K	-	150	250	100	2.1	2.1	680	1170	1900	2400	17.5
NNU4932	4482932	160	220	60	2	2	315	620	2000	2600	6.6
NNU4932K	4382932	160	220	60	2	2	315	620	2000	2600	6.5
NN3032	3282132	160	240	60	2.1	2.1	345	650	1900	2400	8.4
NN3032K	3182132	160	240	60	2.1	2.1	345	650	1900	2400	8.3
NNU4132	-	160	270	109	2.1	2.1	850	1380	1800	2200	25
NNU4132K	-	160	270	109	2.1	2.1	850	1380	1800	2200	24.5
NNU4934	4482934	170	230	30	2	2	330	680	2000	2600	7
NNU4934K	4382934	170	230	60	2	2	330	680	2000	2600	6.9
NN3034	3282134	170	260	67	2.1	2.1	435	810	1900	2400	13.3

Double Row Cylindrical Roller Bearing

NN3034K	3182134	170	260	67	2.1	2.1	435	810	1900	2400	12.9
NNU4134	-	170	280	109	2.1	2.1	880	1500	1600	2000	26
NNU4134K	-	170	280	109	2.1	2.1	880	1500	1600	2000	25.5
NNU4936	4482936	180	250	69	2	2	400	770	1900	2400	11
NNU4936K	4382936	180	250	69	2	2	400	770	1900	2400	10.5
NN3036	3282136	180	280	74	2.1	2.1	550	1000	1800	2200	17
NN3036K	3182136	180	280	74	2.1	2.1	550	1000	1800	2200	16.5
NNU4136	-	180	300	118	3	3	980	1650	1500	1900	33
NNU4136K	-	180	300	118	3	3	980	1650	1500	1900	32.5
NNU4938	4482938	190	260	69	2	2	400	800	1800	2200	11.5
NNU4938K	4382938	190	260	69	2	2	400	800	1800	2200	11
NN3038	3282138	190	290	75	2.1	2.1	560	1000	1600	2000	18
NN3038K	3182138	190	290	75	2.1	2.1	560	1000	1600	2000	17.5